



## ABC Multipurpose 10 LB Dry Chemical Sentry Specifications

Model	AA10S	PK10S	C10S
Agent Capacity	10 lb (4.54 kg) ABC	10 lb (4.54 kg) Purple-K	10 lb (4.54 kg) BC
UL/ULC Rating	4-A:80-B:C	80-B:C	60-B:C
Coast Guard Classification	Type A, Size II Type B, C, Size II	Type B, C, Size II	Type B, C, Size II
Discharge Time	21 seconds	22 seconds	19 seconds
Maximum Effective Range	20 ft (6.1 m)	20 ft (6.1 m)	16 ft (4.9 m)
Operating Temperature Range	-65 °F to 120 °F (-54 °C to 49 °C)		
Agent Flow Rate	0.52 lb/sec (0.24 kg/sec)	0.46 lb/sec (0.21 kg/sec)	0.59 lb/sec (0.27 kg/sec)
Charged Weight with Agent	17 lb, 0 oz (7.73 kg) ABC	17 lb, 14 oz (8.13 kg) Purple-K	17 lb, 14 oz (8.13 kg) BC
Dimensions	20 1/2 in. (521 mm) H 8 1/4 in. (210 mm) W 5 1/4 in. (133 mm) D		

VB= Vehicle Bracket