



ABC Multipurpose 20 LB Dry Chemical Sentry Specifications

Model	AA20-1	PK20	C20
Agent Capacity	20 lb (9.07 kg) ABC	20 lb (9.07 kg) Purple-K	20 lb (9.07 kg) BC
UL/ULC Rating	10-A:120-B:C	120-B:C	80-B:C
Coast Guard Classification	Type A, Size II Type B, C, Size III	Type B, C, Size III	Type B, C, Size III
Discharge Time	28 seconds	30 seconds	21 seconds
Maximum Effective Range	22 ft (6.7 m)	22 ft (6.7 m)	22 ft (6.7 m)
Operating Temperature Range	-40 °F to 120 °F (-40 °C to 49 °C)		
Agent Flow Rate	0.73 lb/sec (0.33 kg/sec)	0.67 lb/sec (0.30 kg/sec)	0.99 lb/sec (0.45 kg/sec)
Charged Weight with Agent	32 lb, 2 oz (14.60 kg) ABC	32 lb, 2 oz (14.60 kg) Purple-K	32 lb, 2 oz (14.60 kg) BC
Dimensions	22 1/2 in. (571 mm) H 9 1/2 in. (241 mm) W 7 7/32 in. (183 mm) D		

VB= Vehicle Bracket