



## ABC Multipurpose 5 LB Dry Chemical Sentry Specifications

Model	AA05S-1	AA05S-1 VB	PK05S
Agent Capacity	5 lb (2.27 kg) ABC	5 lb (2.27 kg) ABC	5 lb (2.27 kg) Purple K
UL/ULC Rating	3-A:40-B:C	3-A:40-B:C	60-B:C
Coast Guard Classification	Type A, Size II Type B, C, Size I	Type A, Size II Type B, C, Size I	Type B, C, Size I
Discharge Time	14 seconds	14 seconds	17 seconds
Maximum Effective Range	14 ft (4.3 m)	14 ft (4.3 m)	16 ft (4.9 m)
Operating Temperature Range	-65 °F to 120 °F (-54 °C to 49 °C)		
Agent Flow Rate	0.36 lb/sec (0.16 kg/sec)	0.36 lb/sec (0.16 kg/sec)	0.30 lb/sec (0.14 kg/sec)
Charged Weight with Agent	9 lb, 1 oz (4.12 kg) ABC	9 lb, 1 oz (4.12 kg) ABC	9 lb, 1 oz (4.12 kg) Purple K
Dimensions	16 3/4 in. (425 mm) H 8 1/2 in. (216 mm) W 4 7/16 in. (113 mm) D		

VB= Vehicle Bracket